

Series	SL (Slimline)	DM (DC-Miniature)	E (Economy)	SR (Standard Range)	SB (Short Body)	TD (Turbine Detector)	HI (Heavy Industrial)	SHI (Short Heavy Industrial)	SLM (Slimline Pressure Proof)
A.C. Type	✓		✓	✓	✓	✓	✓	✓	✓
D.C. - D.C. Type		✓	✓ (DE)	✓ (DR)					
Range (Smallest)	5mm	5mm	5mm	25mm	25mm	10mm	25mm	150mm	50mm
Range (Largest)	50mm	50mm	600mm	600mm	150mm	75mm	250mm	600mm	150mm
Free Core	✓	✓	✓						
Free Core & Extension	✓	✓	✓						✓
Guided Core & Extension	✓	✓	✓	✓	✓				
Sprungloaded	✓	✓		✓	✓	✓			
Rolling Ball End				✓	✓				
Spherical End	✓	✓							
Rod End Bearings				✓	✓		✓	✓	
Wires	✓	✓	✓			✓			
Plain Cable		✓	✓	✓	✓	✓	✓	✓	
Armoured Flexible Conduit				✓	✓	✓	✓	✓	
Connector		✓		✓	✓	✓	✓	✓	✓
End Exit	✓	✓	✓	✓		✓			✓
Side Exit		✓		✓	✓	✓	✓	✓	✓
Waterproof (IP68)		✓ (DM-W)		✓ (SR-W / DR-W)		✓ (Conduit)			
Standard Temperature	90°C	80°C	150°C	150°C / 170°C	150°C / 180°C	150°C	150°C / 180°C	150°C / 180°C	150°C / 180° C
High Temperature						✓ (HTD 200°C)			