



- ROBUST INDUSTRIAL DESIGN
- 4 – 20 mA LOOP POWERED
- VELOCITY VIBRATION UP TO 50mm/s
- LINEARITY WITHIN $\pm 1\%$
- ATEX APPROVAL Ex ia IIC T4
- FREQUENCY RANGE 2.5Hz to 6KHz
- 120 °C OPERATION

The PZDC series of vibration transducers are compact and robust sealed instruments providing a process output of 4-20mA proportional to RMS velocity vibration. The series are designed for applications requiring direct integration in to SCADA systems (PLC/DCS) and provide an extremely cost effective solution for measuring overall vibration performance.

A simple two-wire loop signal proportional to current provides the electrical interface; the velocity vibration range is factory set between 15mm/s and 50mm/s. Utilising Sensonics compression mode technology the sensors offer an extremely linear performance over the full dynamic range and accuracy to within a few percent.

The outer case is constructed from stainless steel and is hermetically sealed and electrically isolated from the signal connectors which are made by top exit cable or a 2 pin MIL style connector. The transducer is mounted by means of a single threaded hole in the base of the cylindrical body; this accepts a mounting stud which can be supplied by Sensonics.

PZDC VELOCITY TRANSDUCER

SPECIFICATION

Operating Voltage.....	16 to 32 volts DC.
Output signal.....	4-20mA proportional to output ranges
Output ranges.....	0 – 15mm/s, 20mm/s, 25mm/s & 50mm/s (g available)
Accuracy	±5%
Frequency Range	10Hz to 1kHz (1dB), 2.5Hz to 6kHz (3dB)
Transverse sensitivity	Less than 5%
Temperature sensitivity	0.05% per °C
Residual electrical noise	Less than 0.2mg (2.5Hz to 10kHz)
Signal transmission	Two-wire system, electrically isolated from body up to 500Vac.
Weight.....	225 gms (nominal)
Certification ATEX	CE Ex II 1G (Ex ia IIC T4) Tamb = 80°C

Environmental

Acceleration limit: Vibration.....	200g pk at 120Hz for 10 mins
Temperature: Operation	-30°C to +120°C (IP68 version -30°C to +80°C)
Survival	-55°C to +140°C
	NB. Certain types of connector or cable may limit the temperature performance of the transducer, see IS. Sheet for details.
Protection (BS.EN60529).....	Sealed to IP.66 / IP.67 (also IP68 version available)

ORDERING INFORMATION

PZDC -

A	B	C	D	E	F
5					

A Electrical Configuration

5

 - 2 wire ICP 4-20mA loop power

B Connection Method

- | | | |
|---|---|--|
| 6 | A | Integral Cable (80°C) Unarmoured |
| 6 | B | Integral Cable (80°C) Armoured |
| 6 | C | Integral Cable (140°C) Unarmoured |
| 6 | D | Integral Cable (140°C) Armoured |
| 7 | G | Integral Cable/Waterproof Gland (80°C)
Unarmoured (IP68 Option) |
| 8 | E | Integral MIL Conn |

C Cable length (Specify in whole metres)

0	2
---	---

 e.g. = 2 metres (max 25 metres)

D Output Range

- | | |
|---|-------------|
| 1 | 0-15 mm/sec |
| 2 | 0-20 mm/sec |
| 3 | 0-25 mm/sec |
| 4 | 0-50 mm/sec |

E Mounting Thread (Female)

- | | |
|---|---------|
| 1 | - M8 |
| 2 | - ¼ UNF |

F Hazardous Area Approval

- | | |
|---|-----------------------------|
| 0 | - Non Intrinsic |
| 1 | - Intrinsically Safe Option |

DS1111_7



Sensonics Ltd
 Northbridge Road
 Berkhamsted
 Herts, HP4 1EF
 United Kingdom
 Tel: +44 (0)1442 876833
 Fax: +44 (0)1442 876477
www.sensonics.co.uk