



- SINGLE POINT MOUNT, SIDE ENTRY, EASY INSTALLATION
- LOW COST HEAVY DUTY PROTECTION
- EXTREMELY LOW PROFILE
- DUAL CASE, LOW NOISE
- STAINLESS STEEL HERMETICALLY SEALED OUTER CASE
- FREQUENCY RANGE 0.4Hz TO 11KHz
- INTERNALLY SHIELDED
- ELECTRICAL AND THERMAL ISOLATION
- SHEAR MODE OPERATION
- INTRINSICALLY SAFE OPTION CE Ex II 1G (EEx ia IIC T4)

The PZS4 accelerometer is intended to satisfy the general specification requirements for a low cost vibration transducer for use especially in multi-point harsh environment industrial vibration monitoring applications.

The two-wire current-loop operating principle permits very long interconnecting cables to be used where necessary and at minimum expense since standard screened pair (or multi-pair) cables may be used.

The piezo-electric shear mode sensor and amplifier are contained within an inner metal enclosure, which is electrically and thermally insulated from the outer stainless steel body. The arrangement prevents earth loops and eliminates electrical interference, and minimises thermal shocks and base strain. The inner enclosure is connected to the 0V of the two wire system and is therefore an effective electrical screen. External connections are made via a side exit integral cable or electrical connectors.

PZS4 ACCELEROMETER

SPECIFICATION

Operating Voltage/current	18 to 28 volts D. C. constant current source of 2 to 10mA
Output signal	100mV/g
Bias Voltage	12Vdc $\pm 20\%$
Dynamic Range	Up to 70g peak (at 24Vdc input)
Frequency Range	0.4Hz to 11KHz (better than 3dB) (standard)
Transverse sensitivity	Less than 5%
Amplitude linearity	$\pm 1\%$ or better
Temperature sensitivity	Less than 8% up to 140°C
Residual electrical noise	Less than 0.2mg (2.5Hz to 11KHz)
Signal transmission	Two-wire system, 500Vac electrical isolation from body Connector variants, contact Sensonics for details
Weight.....	150 gms (nominal)

Environmental

Acceleration limit:	Vibration	200g pk at 120Hz for 10 mins
	Shock	500g half sine without connector
Temperature:	Operation	-30°C to +140°C (Intrinsic version -30°C to +100°C)
	Survival.....	-55°C to +160°C
		NB. Certain types of connector or cables may limit the temperature performance of the transducer, see IS. Sheet for details.
Protection (BS.EN60529).....		Sealed to IP.66 / IP.67
Certification ATEX.....		CE Ex II 1G (EEx ia IIC T4) Tamb = 100°C

ORDERING INFORMATION

PZS4 -

A
2

B

C

D

E

F

A Electrical Configuration

2

 - 2 wire ICP device

C Cable length (Specify in whole metres)

0

2

 e.g. = 2 metres (max 25 metres)

0

0

 - for no cable length, i.e. connector versions of instrument

B Connection Method

6

A

 Integral Cable (80°C) Unarmoured

6

B

 Integral Cable (80°C) Armoured

6

C

 Integral Cable (140°C) Unarmoured

6

D

 Integral Cable (140°C) Armoured

8

E

 Integral Connector, 2 pin, circular, threaded

--

--

7

A

 Integral Cable/Waterproof Gland (80°C)
Unarmoured (IP68 Option)

D Output & Frequency band (3dB point)

1

 100mV/g $\pm 10\%$ (0.4Hz - 11KHz)

2

 100mV/g $\pm 5\%$ (0.4Hz - 11KHz)

E Captive Mounting Bolt

1

 - ¼ UNF

2

 - M6

3

 - M8

F Hazardous Area Approval

0

 - Non Intrinsic

1

 - Intrinsically Safe ATEX. (see restrictions below)

DS1135_7



Sensonics Ltd
Northbridge Road
Berkhamsted
Herts, HP4 1EF
United Kingdom
Tel: +44 (0)1442 876833
Fax: +44 (0)1442 876477
www.sensonics.co.uk